




Single Split Couplings

A better method of holding two shafts together in an axial plane. The clamping power provides a method of holding the shafts without damage to the shaft. Relief cuts are provided on all of these one piece couplings. All of these can be re-bored to special and/or close metric dimensions.



Available Bore Sizes: 1/4" through 2"

Available Finishes: Stainless Steel and Black Oxide

Black Oxide	Stainless	Bore I.D.	O.D.	Width In.	Set Screw
S1C-025-025-BLA	S1C-025-025-SS	1/4-1/4	11/16	1-1/8	4-40x3/8
S1C-037-025-BLA	S1C-037-025-SS	3/8-1/4	7/8	1-3/8	4-40x3/8
S1C-037-037-BLA	S1C-037-037-SS	3/8-3/8	7/8	1-3/8	6-32x3/8
S1C-050-037-BLA	S1C-050-037-SS	1/2-3/8	1-1/8	1-3/4	8-32x1/2
S1C-050-050-BLA	S1C-050-050-SS	1/2-1/2	1-1/8	1-3/4	8-32x1/2
S1C-062-050-BLA	S1C-062-050-SS	5/8-1/2	1-5/16	2	10-32x1/2
S1C-062-062-BLA	S1C-062-062-SS	5/8-5/8	1-5/16	2	10-32x1/2
S1C-075-050-BLA	S1C-075-050-SS	3/4-1/2	1-1/2	2-1/4	1/4-28x5/8
S1C-075-062-BLA	S1C-075-062-SS	3/4-5/8	1-1/2	2-1/4	1/4-28x5/8
S1C-075-075-BLA	S1C-075-075-SS	3/4-3/4	1-1/2	2-1/4	1/4-28x5/8
S1C-087-062-BLA	S1C-087-062-SS	7/8-5/8	1-5/8	2-1/2	1/4-28x5/8
S1C-087-087-BLA	S1C-087-087-SS	7/8-7/8	1-5/8	2-1/2	1/4-28x5/8
S1C-100-050-BLA	S1C-100-050-SS	1-1/2	1-3/4	3	1/4-28x5/8
S1C-100-075-BLA	S1C-100-075-SS	1-3/4	1-3/4	3	1/4-28x5/8
S1C-100-100-BLA	S1C-100-100-SS	1-1	1-3/4	3	1/4-28x5/8
S1C-112-100-BLA	S1C-112-100-SS	1-1/8-1	1-7/8	3-1/8	1/4-28x5/8
S1C-112-112-BLA	S1C-112-112-SS	1-1/8-1-1/8	1-7/8	3-1/8	1/4-28x5/8
S1C-125-100-BLA	S1C-125-100-SS	1-1/4-1	2-1/16	3-1/4	1/4-28x5/8
S1C-125-125-BLA	S1C-125-125-SS	1-1/4-1-1/4	2-1/16	3-1/4	1/4-28x5/8
S1C-137-100-BLA	S1C-137-100-SS	1-3/8-1	2-1/4	3-1/2	1/4-28x5/8
S1C-137-137-BLA	S1C-137-137-SS	1-3/8-1-3/8	2-1/4	3-1/2	1/4-28x5/8
S1C-150-100-BLA	S1C-150-100-SS	1-1/2-1	2-1/2	3-3/4	1/4-28x5/8
S1C-150-150-BLA	S1C-150-150-SS	1-1/2-1-1/2	2-1/2	3-3/4	1/4-28x5/8
S1C-175-175-BLA	S1C-175-175-SS	1-3/4-1-3/4	3	4-1/2	5/16-24x7/8
S1C-200-200-BLA	S1C-200-200-SS	2-2	3-1/4	4-7/8	5/16-24x7/8

NOTE: Couplings with a straight bore (i.e. S1C-100-100-BLA) can be broached for keyway.

www.daytonsuperiorproducts.com